



Features

- ✓ 5.6" TFT LCD Display
- ✓ 320 x 234 - 65,536 colours
- ✓ Touch screen
- ✓ 32 bits RISC 400MHz CPU Fan-less
- ✓ LED Back Light
- ✓ 1 x USB 2.0 Device
- ✓ 1 x Serial port (RS232/RS485 2W/4W)
- ✓ Built-in Power Isolator

Specification

System

CPU	32Bits RISC 400MHz processor
Memory	64MB DDR2 on board
Cooling System	Fan-less

Display

Display	5.6" TFT LCD
Luminance	300cd/m ²
Colours	65,536
Contrast Ratio	300:1
Resolution	320 x 234
Viewing angle	45°/65°/65°/65° (Top/Bottom/Left/Right)
Backlight	LED
Backlight Lifetime	30,000 hours

Touch Screen

Type	4 wires Analog Resistive
Lifetime	1 million touch (with finger) minimum

I/O

Serial Port	1 x COM (RS-232 / RS-485 2W / RS-485 4W)
USB Port	1 x USB 2.0 Device - Mini USB format

Storage

Flash Memory	128MB Flash Memory on board Application size up to 16MB Data and Event Log size up to 48MB
---------------------	--

Mechanical

Construction	Plastic molding housing
Dimensions	204mm x 150mm x 48mm (W x H x D)
Mounting Method	Panel mount VESA 75 mount
Panel Cutout	192mm x 138mm (W x H)
Weight (net)	0.85Kg
Power Supply	DC 24 V +/- 20% (19.6~28.8V DC)
Power Consumption	250mA @ 24V

Environment

Storage Temp.	-20~60°C (-4~140°F)
Operating Temp.	0~45°C (32~113°F)
Relative Humidity	10~90% @ 40°C non-condensing
Vibration	2G peak, 10~25 Hz (X, Y, Z directions, 30 minutes)

Certifications

Front Panel	NEMA 4 IP 65
EMC	CE (EN50081-2 & EN50082-2 standards) FCC Class A

Programming Framework

Software	ViewBuilder8000 v3.0.0 or newer
-----------------	---------------------------------

Ordering Information

PV6056i	5.6" 320 x 234 TFT LCD HMI, 64 DDR2 RAM, 128MB Flash memory on board
RZCPV6100	Cable required to download application by USB port, Mini USB to USB 2.0, 1m cable